

SKC Sampling Solutions

For Confined Space Entry Monitoring

Recognition

In terms of workplaces, confined spaces have limited or restricted means of entry and exit and are not designed for continuous occupancy. Examples of confined space include tanks, vessels, silos, pits, manholes, tunnels, ductwork, and pipelines. These spaces may be poorly ventilated and contain insufficient oxygen or hazardous levels of toxic gases.

See the SKC equipment recommended for detecting or monitoring gases in confined space entry.

Evaluation with SKC Sampling Solutions

For over 50 years, SKC has led the research, design, and manufacture of quality sampling equipment and media to aid health and safety professionals in the evaluation of occupational and environmental hazards.

Choose from the SKC sampling solutions for confined space entry monitoring, which include a selection of portable gas monitors and detectors.

Portable Instruments



See reverse side for sampling equipment.



Confined Space Entry Monitoring

Sample Instruments

Monitoring Solutions

For Detecting/Monitoring	Instrument and SKC Cat. No.	Notes
LEL, O ₂ , H ₂ S, CO, SO ₂ , or HCN	QRAE 3 Pumped Multi-gas Monitor 730-20-11111-111	
HF, HCl, H ₂ O ₂ , or hydrazine	X-am® 5100 Personal Single-gas Detector 805 Series	
H ₂ S or CO	ToxiRAE 3 Single-gas Monitor 730 Series	
O ₂ , CO, or H ₂ S	Pac 5500 Personal Gas Detector 805 Series	Unlimited service life, replaceable sensors with 3-year warranty
	Pac 3500 Personal Gas Detector 805 Series	2-year service life, permanent sensors with 2-year warranty
O ₂ , CO, H ₂ S, and LEL	X-am Personal Gas Detectors 805 Series: X-am 2500 for 1 to 4 gases X-am 5000 for 1 to 5 gases X-am 5600 for 1 to 6 gases	Optional external pump for clearance measurements
O ₂ , CO, H ₂ S, HCN, PH ₃ , CO ₂ , SO ₂ , NO ₂ , Cl ₂ , NH ₃ , NO, and organic vapors	Pac 7000 Personal Gas Detector 805 Series	

